



HT1

Rugged Handheld Terminal

unitech electronics co., ltd., a leading global provider of automatic identification and data capture technologies, has launched its latest compact handheld terminal, HT1. It is a pocket-sized mobile computer with superior data collection solution, suitable for a wide range of applications including retail, transportation and warehousing.

Compact Pocket-Sized Design

Coming with intelligent imaging technology for high-performance scanning, the HT1 ensures read reliability for mobile phone screens and paper in any orientation. Running with Android 4.4 operating system, HT1 has a 2-inch LCD display that supports 240x320 pixel resolutions, allowing users to get feedback of the scanned information immediately. Base on its pocket-sized design for one-handed operation, it is highly portable with simple keyboard layout that is easy to carry around and easier typing. HT1 is an ideal tool to automate the capture of inventory data and allows user to take action quickly and accurately.

Reliable and Durable

Engineering with industrial materials, HT1 is rugged enough to withstand multiple 5 feet drop to concrete and equipped with IP54 environmental seal against water and dust. Featuring a great adaptable design, the device provides multiple wireless communications such as wireless LAN a/b/g/n radio that ensures seamless wireless data transmission and real-time collections to back-end system. Combing with multi-functionality and lightweight design, unitech HT1 perfectly reflects its high performance at a best available price.

Versatile MDM solutions

It also supports Mobile Device Management (MDM) solutions, users can easily remote to set up, update, monitor and troubleshoot all of your devices. It is ideal for use to do garment processing, food order taking, logistics controlling and inventory management. Combing functionality with durable design, the unitech HT1 provides the power for enterprise to streamline business processes and increase productivity and efficiency in all data collection applications.

Features

- 2" ergonomic handheld terminal with Android 4.4 operating system
- Integrated superior 1D/2D barcode imaging technology
- Ergonomic design for one-handed operation, 30 degree scanning tilt
- Support 12Management and MoboLink, Airwatch, SOTI
- Built in Robust Pogo pins and Micro USB (Support OTG)
- WLAN IEEE 802.11 a/b/g/n
- Rugged Construction: IP54 rated and 1.5M drop certified



► **System Features**

| | |
|-------------------|---|
| CPU | Freescale iMx6 1.2GHz |
| Memory | 1GB DDR2 4GB eMMC |
| OS | Android 4.4.3 |
| Languages support | English, Simp. Chinese, Traditional Chinese, Japanese |

► **Display**

2" TFT 240X320 LCD

► **Keypad**

10 numeric keys, scan keys, Alpha / Power (on/off) / Enter key, 4 function keys

► **Indicator**

Green and Red LED located above LCD
Vibrator

► **Symbologies**

2D Imager

| | |
|----|--|
| 1D | All major codes |
| 2D | PDF417, MicroPDF417, Composite, RSS, TLC-39, Datamatrix, QR code, Micro QR code, Aztec, MaxiCode, Postal Codes: US PostNet, US Planet, UK Postal, Australian Postal, Japan Postal Dutch Postal (KIX) |

30 degree scanning tilt

► **Audio**

Speaker & MIC

► **Interface**

| | |
|------|---|
| USB | Micro USB connector (OTG interface, have USB Client and USB Host function) |
| PoGo | PoGo pin for charging |

► **Communication**

| | |
|------|---------------------|
| WLAN | IEEE 802.11 a/b/g/n |
|------|---------------------|

► **Power Source**

| | |
|--------------|---|
| Battery type | Li-ion battery Detachable with back cover all in one |
| Capacity | 1100mAh 4540mAh (Option) |

► **Enclosure**

| | |
|-----------|----------------------------------|
| Weight | 170g |
| Dimension | 147.8(L) x 53.8(W) x 30.31(H) mm |

► **Environmental**

| | |
|-------------------------|---|
| Operating temp. | -10°C~50°C |
| Operating humidity | 20%~85% |
| Storage temp. | -30°C~70°C |
| Storage humidity | 20%~85% |
| Drop | 1.5m |
| Water proof, dust proof | IP54 |
| Vibration | During operation: 0.5G, 3 to 100Hz, 1 min sweep, during 15min, 3 direction Non-operation: 1.5G, 5 to 55Hz, 1min sweep, during 120min, 3 direction Non-operation: 1.5G, 5 to 1000Hz, 1min sweep, during 15min, 3 direction |
| Magnetic field | 1gauss |
| EMC | Air discharge: 16kV Direct discharge: 9KV |

► **Accessories**

Single Slot cradle
4-Bay Battery Charger (Option)
USB Cable/USB Adapter & Plugs
Hand Strap
AC Power Adapter

► **Regulatory Approvals**

CE, FCC, BSMI, PSE



Headquarters

Taipei, Taiwan
<http://www.ute.com> e-mail: info@hq.ute.com

unitech America

Los Angeles
<http://us.ute.com> e-mail: info@us.ute.com
<http://can.ute.com> info@can.ute.com
Mexico
<http://latin.ute.com> e-mail: info@latin.ute.com

unitech Asia Pacific & Middle East

Taipei
<http://apac.ute.com> info@apac.ute.com / info@india.ute.com
<http://mideast.ute.com> info@mideast.ute.com

unitech Europe

Tilburg / Netherlands
<http://eu.ute.com> e-mail: info@eu.ute.com

unitech Japan

Tokyo
<http://jp.ute.com> e-mail: info@jp.ute.com

unitech Greater China

Beijing, Shanghai, Guang Zhou, Xiamen
<http://cn.ute.com> info@cn.ute.com
Taipei <http://tw.ute.com> info@tw.ute.com

